



iQS 6045V | 45RU 600w x 1000d Cabinet

The iQ Series is a premium quality cabinet range providing flexible solutions for a variety of applications.

The cabinets are aisle containment ready with mounting holes in place for optional accessories including vertical air dams, vertical cable management and base plates.

The cabinets can be equipped with the Racktech iQ cable management system ideal for large volumes of cables and patch leads.

Features

- Strong frame designed with heavy-gauge mounting rails enable 1400kg static loads with levelling feet and 1000kg dynamic loads with castors
- Vented front door with curved profile allows for more airflow with 70% perforation
- Integrated Electrical Grounding for roof, side panels, doors and frame
- Vertical mounting rail and integrated alignment feature enables quick installations
- Noof panel is reversible to reposition the larger cable entries if required
- Large cable access entry points in the roof provides access for overhead cable egress
- Fans, castors, cable managers, PDU trays and chimneys are available
- > Black is the standard colour. Other colours are available upon request. MOQ applies.

Standard Inclusions


- > Curved vented front door
- Split vented rear door
- > Split side panels
- Top panel
- > Front and rear mounting rails
- > Levelling feet (set of 4)

Technical Specifications

Description:	iQ Cabinet 45RU 600w 1000d		
Cabinet Dimension:	2079h x 600w x 1090d		
Colour:	Black		
Frame Weight:	116kg		
Shipping Dimension:	2119h x 640w x 1130d		
Shipping Weight:	120kg (Note: weight of cabinet will vary according to selected accessories)		



Typical iQ Series Cabinet



Top panel showing cable access areas

Two – 130 x 448mm, Six – 100 x 100mm, Four – 60mm Ø



iQS 6045V Cabinet Dimensions

Cabinet Width RU (mm)	Width	Overall Depth (mm)		Overall Height (mm)		
	Frame to Frame	Door to Door	On Frame	On Levelling Feet	On Castors	
45RU	600	1000	1090	2079	2099	2127

iQ Series Construction

Frame

- > Strong frame design with heavy-gauge mounting rails
- > Static load ratings 1400 kg on levelling feet
- > Dynamic load ratings 1000 kg with castors

Doors

- > Split rear doors improve access and serviceability to rear of rack mounted equipment
- > Simple lift-off front door design with swing to 155°
- > Front door can be hinged on the left or right hand side or interchanged with rear door
- > Doors are fitted with swing handle and lock

Mounting rails and brackets

- > Vertical mounting rails can be easily adjusted
- > RU positions are numbered on front and rear mounting rails to help with quick installation

Side Panels

- > Half height quick release side panels reduce size and weight for easy handling and access
- > Side panels are lockable using a single key provided



Split Side Panels





Rail Alignment Feature



Optional Vertical Cable Managers



Optional PDU Tray



Integrated Electrical Grounding



Adjustable Mounting Rail



Information contained in this document is accurate at the time of preparation and is provided in good faith for general guidance. The information should not be used for detailed design or final specification as it is subject to change without notice. Please contact your local Racktech sales representative or the Racktech customer support team to obtain a copy of the current technical specifications. Images are for illustration purposes only.