

IQDG-MTV-1623K-16N1 | Monitored PDU 16Amp 230V

Meter:	True RMS Current Meter
Power Monitor:	Total Power Monitoring by Meter. Web, SNMP, Free Bundle Software
Protocols:	TCPIP, SNMP, DHCP, UDP
Alarm Thresholds:	User-Defined Alarm Thresholds for Warning and Overload
Event Alert:	Email, Trap, Audible Alarm
GENERAL	
Output:	(14) IEC320 C13 (2) IEC320 C19
Input:	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord, 3 meter longs
COMMUNICATION	
DHCP Indication:	(3) Green LED
Network:	(1) RJ45 for Ethernet
Circuit Status	(1) Red LED
Temp./Humidity	(1) RJ11 for ENV probe connection
Current Meter:	3 Digits Meter Range: 0A ~ 20A Resolution: 0.1A Precision: +/- 2% +/- 0.1 Amp
OPERATION	
Nominal Voltage:	230V
Voltage:	200V~240V
Frequency:	50/60HZ full range
Max. Output:	16Amp Current
Temperature:	0 ~ 45° Celsius
Humidity:	0% ~ 90%
Size:	56 x 1245 x 44 mm
Weight:	1.5 kg



Information contained in this document is accurate at the time of preparation and is provided in good faith for general guidance. The information should not be used for detailed design or final specification as it is subject to change without notice. Please contact your local Racktech sales representative or the Racktech customer support team to obtain a copy of the current technical specifications. Images are for illustration purposes only.

