

iQDG-SWH-1023J-08NI | Switched PDU 10Amp 230V

Meter:	True RMS Current Meter
Power Monitor:	Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols:	TCPIP, SNMP, DHCP, UDP
Outlet Control:	Individual
Power Delay:	Power on/off sequence can define
Alarm Thresholds:	User-Defined Alarm Thresholds for Warning and Overload
Event Alert:	Email, Trap, Audible Alarm
GENERAL	
Output:	(8) IEC320 C13
Input:	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C14 power cord, 3 meters long
Protection:	(1) 10 Amp Circuit Breaker
COMMUNICATION	
DHCP Indication:	(1) Green LED
Output Status:	(8) Green LED
Network:	(1) RJ45 for Ethernet
Current Meter:	3 Digits Seven Segment Range: 0A ~ 20A Resolution: 0.1A Precision: +/- 2% +/- 0.1 Amp
OPERATION	
Nominal Voltage:	230V
Voltage:	200V~240V
Frequency:	50/60HZ full range
Max. Output:	10Amp Current
Temperature:	0 ~ 40° Celsius
Humidity:	0% ~ 90%
Size:	90 x 432 x 44 mm
Weight:	2 kg



Information contained in this document is accurate at the time of preparation and is provided in good faith for general guidance. The information should not be used for detailed design or final specification as it is subject to change without notice. Please contact your local Racktech sales representative or the Racktech customer support team to obtain a copy of the current technical specifications. Images are for illustration purposes only.

